


## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: GI10056L

**Model Number:** MG01X4W1-30PN63-3PS56B2A10-S-A

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 32A, 230/400V WYE, 22.0kW

**Physical Configuration:** 72in / 1829mm, Vertical

**Product Summary:** rPDU, Basic Upgradeable, 32A, 230/400V WYE, 22.0kW, Vertical, (24) Locking IEC C13, (6) Locking IEC C19, 3m power cord with 3P+N+E (IP44), Black Powder Coat.

**Monitoring:** No Monitoring (Upgradeable with IMD module)

### Plug Form:



3P+N+E (IP44)

### Receptacle:



Locking IEC C13  
(Quantity: 24)



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

**Monitoring** No Monitoring (Upgradeable with IMD module)

|  |   |
|--|---|
| <b>Quantity Of Inputs</b>                                    | 1   |
| <b>Voltage</b>   | 200-240/346-415V WYE  |
| <b>Current</b>   | 32A x 3 Phase WYE   |
| <b>VA per Input (Load Capacity)</b>                          | 22.0kW (230V)   |
| <b>Frequency</b>   | 50/60Hz   |
| <b>Over Current Protection</b>                               | (6) 16A Single Pole Magnetic Breakers   |
| <b>Switch</b>  | Breaker/Switch Combination  |
| <b>Power Cable Wire Gauge</b>                                | 6mm <sup>2</sup> H07RN-F  |
| <b>Power Cable Length</b>                                    | 10ft / 3m   |
| <b>Power Entry Location</b>                                  | Bottom Front  |
| <b>Plug Type</b>   | IEC60309 3P + N + E, 32A, 230/400V, Splashproof IP44  |
| <b>Combined Total Receptacle/Socket Quantity</b>             | 30  |
| <b>Alternating Phase/Circuits</b>                            | Yes   |
| <b>Receptacle/Socket Type #1</b>                             | U-Lock IEC C13  |
| - Quantity on Face   | 24  |
| - Quantity per Breaker                                       | 4   |
| - Quantity per Phase   | 8   |
| - U-Lock Color ID  | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue                                    |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                              | 230V  |
| <b>Receptacle/Socket Type #2</b>                             | U-Lock IEC C19  |
| - Quantity on Face   | 6   |
| - Quantity per Breaker                                       | 1   |
| - Quantity per Phase   | 2   |
| - U-Lock Color ID  | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue                                    |
| - Style  | Individual  |
| - Voltage per Receptacle/Socket                              | 230V  |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F  |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black   |
| <b>Configuration</b>   | 72in / 1829mm Vertical Rackmount  |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 1556mm and 1645mm   |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>                        | CE Marked   |
| <b>Certification/Agency Approvals</b>                        | Complies with EN 55032 and EN 55024   |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>                        | RCM Mark (EMC Only)   |
| <b>Certification/Agency Approvals</b>                        | Complies with IEC 62368-1 (DOC Available)   |
| <b>Certification/Agency Approvals</b>                        | China RoHS  |
| <b>Certification/Agency Approvals</b>                        | C <sub>p</sub> Mark   |

|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>Chassis Dimensions (LxWxD)</b> | <b>1829mm x 51mm x 58mm</b> |
| <b>Shipped Weight</b>             | <b>19lbs (8.62kg)</b>       |