

OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: G2242

Model Number: MG0AXER1-10I823-3PS6B2H10-S

Category: Metered

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary: rPDU, Metered Standard, 32A, 230V, 7.3kW, Horizontal, (8) IEC C13, (2) IEC C19, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

Monitoring: Current - Local
Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

Plug Form:



1P+N+E (IP44)

Receptacle:



IEC C13
(Quantity: 8)



IEC C19
(Quantity: 2)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Monitoring	Current - Local
	Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input
Monitoring Level 1	Aggregate - Total Unit Monitoring
Quantity Of Inputs	1
Voltage	200-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz
Over Current Protection	(2) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	4mm ² H07RN-F
Power Cable Length	3m
Plug Type	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
Combined Total Receptacle/Socket Quantity	10
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	8
- Quantity per Breaker	4
- Style	Banks of 2
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC C19
- Quantity on Rear	2
- Quantity per Breaker	1
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	60C / 140F
Heavy Steel - Powder Coat Finish	Black
Configuration	19in / 483mm Horizontal Rackmount
Flush Mount	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with EN 55032 and EN 55024
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	RCM Mark (EMC Only)
Certification/Agency Approvals	Complies with IEC 62368-1 (DOC Available)
Certification/Agency Approvals	C _p Mark
Chassis Dimensions (HxWxD)	44mm x 435mm x 100mm
Shipped Weight	5lbs (2.27kg)