

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: G2202

**Model Number:** MG00X4A1-16IB43-3PS6B2A10-S

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 39in / 978mm, Vertical

**Product Summary:** rPDU, Basic Standard, 32A, 230V, 7.3kW, Vertical, (12) IEC C13, (4) IEC C19, 3m power cord with 1P+N+E (IP44), Black Powder Coat.

### Plug Form:



1P+N+E (IP44)

### Receptacle:



IEC C13  
(Quantity: 12)



IEC C19  
(Quantity: 4)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	200-240V

<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	7.3kW (230V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	None
<b>Over Current Protection</b>	(2) 16A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	4mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	3m
<b>Plug Type</b>	IEC60309 1P + N + E, 32A, 250V, Splashproof IP44
<b>Combined Total Receptacle/Socket Quantity</b>	16
<b>Receptacle/Socket Type #1</b>	IEC C13
- Quantity on Face	12
- Quantity per Breaker	6
- Style	2 Banks of 2, 2 Banks of 4
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
<b>Receptacle/Socket Type #2</b>	IEC C19
- Quantity on Face	4
- Quantity per Breaker	2
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
<b>Maximum Operating Temperature</b>	60C / 140F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	39in / 978mm Vertical Rackmount
<b>GE Vertical Mounting Bracket</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	933.45mm
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55024
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	RCM Mark (EMC Only)
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1 (DOC Available)
<b>Certification/Agency Approvals</b>	C <sub>p</sub> Mark
<b>Chassis Dimensions (LxWxD)</b>	978mm x 51mm x 51mm
<b>Shipped Weight</b>	9lbs (4.08kg)